

Ground Cable kits

Standard cable clamp and cable shown below.



Description	Clamping range	Continuous Current	Tested short circuit withstand	Weight ea.
1" Bronze "C" clamp	.12" - 1.12" [3mm - 29mm dia.]	400RMS amps, 60Hz	43kA/ 250ms	1.9lbs. [.9kg.]

Other clamp options available, call for more information






Description	Strand diameter	Diameter w/jacket	Continuous Current	Tested short circuit withstand	Weight ft.
1/0 - 1064W	.45" [11.4mm]	.62" [15.7mm]	250RMS Amps, 60Hz	21kA/250ms	.49lbs. [.22kg.]

Standard cable length: 30' or specify custom length on order form.
Other wire sizes available, call for more information.

See rail clamp specifications on page 2

Ground Cable kits

Rail clamp specifications



Clamping range



#	Description	Clamping range				Tested short circuit withstand	Calculated short circuit withstand
		A	B	C	D		
1	T-Bar rail clamp	1.77-2.95" [45-75mm]	.98-1.49" [25-38mm]	--N/A--	--N/A--	40kA/120ms	28kA/250ms
2L	Diagonal rail clamp, EDC <u>large</u>	2.55-3.34" [65-85mm]	.98-1.96" [25-50mm]	--N/A--	--N/A--	40kA/300ms	40kA/250ms
2S	Diagonal rail clamp, EDC <u>small</u>	1.77-2.55" [45-65mm]	.98-1.45" [25-37mm]	--N/A--	--N/A--	40kA/300ms	40kA/250ms
3	Isolated magnet	--N/A--	--N/A--	--N/A--	--N/A--	30kA/60ms	12kA/250ms
4	Running rail / under clamp w/ pivot handle	--N/A--	--N/A--	--N/A--	5.00-5.75" [127-146mm]	43kA/250ms	43kA/250ms
5	Base rail clamp	--N/A--	--N/A--	.00-.70" [.00-17.8mm]	--N/A--	35kA/50ms	16kA/250ms
6	Magnet	--N/A--	--N/A--	--N/A--	--N/A--	16.8kA/652ms	--N/A--